

■ General Specifications

Item	Specification
Power supply voltage	24 VDC ±15%
Power consumption	7 W max.
Noise resistance	Conforms to IEC61000-4-4. Power supply line: 2 kV
Vibration resistance	10 to 57 Hz with 0.075-mm single amplitude, 57 to 150 Hz with 9.8 m/s ² acceleration, for a total of 60 min in X, Y, and Z directions
Shock resistance	Peak acceleration 15 G, 3 times each in X, Y, and Z directions
Ambient operating temperature	0 to 50°C (with no icing)
Storage temperature	-20 to +70°C (with no icing)
Ambient operating humidity	35% to 85% (with no condensation)(0 to 40°C) 35% to 60% (with no condensation)(40 to 50°C)
Dimensions	190 x 110 x 53.5 mm (W x H x D) (thickness inside panel: 49.0 mm)
Enclosure ratings	Front panel operating section: Equivalent to IP65F, NEMA 4.*
Weight	0.6 kg max.

*Usage may not be possible in places where the unit would be exposed to oil for long periods.

■ Display Capacity

Item	Specification	
Display elements	Character displays	A total of 65,535 per screen Graphics: Continuous straight lines, rectangles, circles, polygons, arcs, sectors
	Fixed character data	With overlapping screens, the total is 524,280 per screen
	Graphics	
	Marks	
	Numerical displays	256 positions per screen, max. 10-digit display (2 words)
	Character string displays	256 positions per screen, max. 1,024 display elements for overlapping screens
	Graph displays	50 positions per screen, capable of displaying signs and percentages
	Analog meters	50 positions per screen, capable of displaying signs and percentages
	Trend graphs	One frame per screen, 50 items per frame (8 items max. for data logging)
	Broken line graphs	One frame per screen, 256 items per frame, 260 points per item
	Lamps	256 positions per screen
	Image library images	256 positions per screen
	Screen types	Touch switches
Numerical settings *1		256 positions per screen (numerical key pad) Total of 256 positions for both numerical and thumbwheel settings
Thumbwheel settings		26 positions per screen
Character string settings		256 positions per screen
Temporary inputs		One position per screen
Alarm lists/histories		Four groups per screen
Recipes		One position per screen
Normal screens		Displays screens registered as normal
Overlapping screens		A maximum of eight screens can be displayed overlapping each other.
Windows		Up to three window screens can be displayed.
Screen attributes	Display history screens	Order of occurrence (1,024 screens max.), order of frequency (255 times max.)
	System startup screen	Displayed when powering ON (or resetting) the PT, and when switching to RUN mode.
	Programming Console screen	Emulates PLC Programming Console functions, capable of being called from RUN mode.
	Screen registration method	By transferring screen data from the NT Support Tool to the PT via serial communications By mounting the Memory Unit and downloading (automatic/manual transfer) data to the PT
Number of screens	Max. number of registered screens: 3,999	
Screen registration method	Screen number	0: No display 1 to 3999: User registered screens (normal, overlapping, windows) 9000: System startup screen 9001: Display history screens, order of occurrence 9002: Display history screens, order of frequency 9020: Programming Console screen 9021 to 9023, 9030: Reserved 9999: Return to previous screen designation
	Saving screen data	Flash memory (PT internal image memory)

OMRON Corporation

FA Systems Division H.Q.

66 Matsumoto
Mishima-city, Shizuoka 411-8511
Japan
Tel: (81)559-77-9181/Fax: (81)559-77-9045

Regional Headquarters

OMRON EUROPE B.V.
Wegalaan 67-69, NL-2132 JD Hoofddorp
The Netherlands
Tel: (31)2356-81-300/Fax: (31)2356-81-388

OMRON ELECTRONICS LLC
1 East Commerce Drive, Schaumburg, IL 60173
U.S.A.
Tel: (1)847-843-7900/Fax: (1)847-843-8568

OMRON ASIA PACIFIC PTE. LTD.
83 Clemenceau Avenue,
#11-01, UE Square,
Singapore 239920
Tel: (65)835-3011/Fax: (65)835-2711

■ Display Specifications

Item	Specification	
Display panel	Display device	Monochrome STN LCD
	Number of dots (resolution)	260 dots horizontally x 140 dots vertically
	Effective display area	117 mm horizontally x 63 mm vertically
	Viewing angle	Left/right direction: 30°, up/down: 30°
	Display color	Black & white (with blue mode)
	Service life	50,000 hours min. (until contrast reduced to 50%)
Backlight (white cold cathode tube)	Automatic turn-OFF	Can be set to turn OFF in 1 to 255 min or to remain ON with screen saver
	Service life	50,000 hours min. (at room temperature, until brightness is reduced to 50%)
	Replacement	Non-replaceable

■ Panel Specifications

Item	Specification	
Touch panel	Number of switches	91 (13 horizontally x 7 vertically)
	Input	Pressure-sensitive
	Threshold force for operation	1 N max.
	Life expectancy	1 million operations min.

■ External Interface Specifications


Communications method	Serial port A	Serial port B
NT Support Tool	Supported	Not supported
PLC	Host Link	Supported
	1:1 NT Link	Supported
	1:N NT Links	Supported
	NT Link, PT Programming Console function	Supported
SBC/personal computer	Memory Links	Supported
Bar Code Reader		Supported

*Connection via RS-422A/485 is possible using the NS-AL002 RS-232C/422A Adapter (connector), which can be connected only to serial port B. (RS-485 connections must use 1:N NT Links.)

■ NT21 Standard Models

Product	Specifications	Model number		
NT21 Programmable Terminal	Monochrome STN	Frame color: beige NT21-ST121-E Frame color: black NT21-ST121B-E		
	Support Tool	Windows 95, 98, Me, NT, or 2000 CD-ROM NT-ZJCAT1-EV4		
Cables	For screen transfer	XW2Z-S002		
	For PLC connection	PT: 9-pin PLC: 9-pin	Cable length: 2 m XW2Z-200T Cable length: 5 m XW2Z-500T	
		PT: 9-pin PLC: 25-pin	Cable length: 2 m XW2Z-200S Cable length: 5 m XW2Z-500S	
		PT: 9-pin PLC: Mini-peripheral	Cable length: 2 m XW2Z-200T-2 Cable length: 5 m XW2Z-500T-2	
		Options	Reflection Protective Sheets	Display area only (5 sheets) NT20M-KBA04
			Chemical-resistive Cover	Silicon cover NT20S-KBA01
Battery			For alarm lists/histories C500-BAT08	
Memory Unit	For screen and system data transfer NT-MF161			
RS-232C/422A Adapter		NS-AL002		

■ Dimensions



Authorized Distributor:

Programmable Terminals

NT21

Small and Smart




PT

Programmable Terminal

Small and Smart

Compact Size, High Performance


Superb functionality with a compact screen size



Versatile I/O and Large-capacity Screen Memory in a Space-saving Size


Small Size, Large Screen

The LCD screen is larger than the OMRON NT20S (increased from 256 x 128 dots to 260 x 140 dots), but the external dimensions and panel cut-out size are the same.




Plenty of Capacity for Saving Graphic Screens

With 512 Kbytes of memory capacity, there is more than ample space for storing screen data.




Two RS-232C Ports

Two RS-232C ports in the NT21 (compared with one in the NT20S) enable simultaneous connection of a PLC, Bar Code Reader, and NT Support Tool (connectable to serial port A only).



Versatile Communications

In addition to the Host Link and 1:1 NT Link communications, the NT21 supports high-speed 1:N NT Links and Memory Link communications.



Function Support Equivalent to That of a Mid-size Operator Interface

Recipe Function

Parts tables on the PT screen can be used to set multiple word data in records, which can then be written to the PLC by a simple PT touch panel operation. For example, the setting parameters for separate models can be edited on the PT, then written to or read from the PLC.



Alarm List/History(*)


An alarm message can be displayed in response to PLC bit status, and the content and time of the message can be stored as an alarm history.



*C500-BAT08 Battery (sold separately) required.

Programming Console Function

The NT21 is equipped with many of the same functions as the SYSMAC PLC Programming Console.




Mathematical Functions

Up to 256 math equations can be stored in the PT processing table to allow automatic PT processing, and the results can be written to the numeral memory table or other destinations. This makes it possible to perform scaling and other mathematical operations automatically in the PT.

Upgraded NT Support Tool Version (-EV4.6)

Enhanced Editing Functions

I/O comments in the I/O tables of the CX-Programmer can be used directly.



I/O comments for designated PLC addresses can be used directly, with no need for CSV file conversion.

•Symbol Manager previews are supported. This function makes it possible to preview symbols (parts created from graphics data).



•Parts can be copied by drag & drop operations of image, library, or mark data.

•The properties of grouped parts can be edited without having to ungroup them.

•Because NT20S and NT31 screen data is compatible with the NT21, existing software assets can be utilized to greatly reduce the number of design steps.

Note: Some data revisions may be required due to size differences.

Highly Reliable Hardware

Long, Maintenance-Free Life (50,000 h)

Conforms to International Standards

The NT21 conforms to the EC Directives, as well as UL, cULus (Class 1 Div2), and C-Tick. The front panel has an enclosure rating equivalent to IP65F.

System and screen data can be stored in NT21 Flash Memory.

Comparison with the NT20S

Model	NT21	NT20S (Previous model)	
Basic functions	Dimensions	190 (W) x 110 (H) x 53.5 (D) mm	
	Resolution	260 x 140 dots (5.2 inches)	256 x 128 dots (4.91 inches)
	Effective display area	117 x 63 mm	112 x 56 mm
	Display color	Black & white (with blue mode)	
	Panel cut-out size (W x H)	178.5 x 100.5 mm	
	Max. number of registered screens	3999	500
	Screen data capacity	512KB	96KB
	Bit memory table	Supported (1,000 entries)	None
	Windows	Supported (3)	None
Display elements	Rectangles, polygons, arcs, sectors	Supported	None
	Painting out	Supported	None
	Image/library displays	256 positions per screen	None
	Analog meters	50 positions per screen	None
	Trend graphs	1 position per screen	None
	Broken line graphs	1 position per screen	None
	Alarm lists/histories	4 positions per screen Note: An optional battery is required.	None
Recipes	1 position per screen	None	
Additional functions	Interlocks	Supported	None
	Mathematical Function	Math equations: Max. 256 (arithmetic functions, logic operations, bit manipulations, comparison operations)	None
	Programming Console function	(Executes functions equivalent to C200H-PR027 and CS1 Programming Consoles.)	None
	High-quality font	Supported	None
	Memory Unit	Supported	None
Communications	Backlight service life	50,000 hours min.	10,000 hours min.
	Memory Links	Supported	Via RS-232C communications
	Bar Code Reader connection	Supported	None
RS-232C ports	2 ports	1 port	